

PRODUCT SPECIFICATION SHEET

WATTS TELEVAR HYDROSTATIC GAUGES FOR OIL TANKS

BRAND:

TOP SPEC:

PAGE

WATTS

Max Flow dal082

Product Description

The Televar gauge is extremely popular for commercial and domestic sites where reliability and accuracy is essential.

Featuring a hand-pump mechanism the gauges do not require any power, and are therefore ideally suited to hazardous environments.

Constructed from High-Impact Plastic but without Ingress-Protection, these gauges should always be fitted inside a weather-proof housing.

With versions available for vertical, or horizontal tanks, each displays the tanks contents as a percentage of the total capacity, and is suitable for tanks from 0.9 m up to 3.0 m in height.

Supplied with 50m of black Polyethylene Connection Tube, and a GRP weighted Nylon Balance Chamber with 3m of NBR suspension tube. Suitable only for tanks that are permanently atmospherically vented.

For all low-viscosity Fuel and Oil products which are compatible with GRP, NBR and Nylon. Bespoke Balance Chambers for aggressive liquids can also be produced to your requirements.



Features

- O Universal remote pneumatic level indicator
- O Min/max tank depth: 900-3000mm
- O For tanks of any shape and height between
- O Tank connection suitable for pipe with O.D.
- O Basic dial in percentage volume for cylindrical tanks O 6 mm Case with 3 external mounting slots tanks

What sort of tank do you have

Horizontal Tank

(Where the surface area of fluid changes at different depths





Vertical Tank

(Where the surface area of the fluid is the same at any depth)





Additional Information	
Max Nozzle Capacity	110lph
Max Return Oil Pumped In To The Tigerloop	120lph
Max Flow	230lph
Max De-Aerating Capacity	8lph
Max Operating Temperature	60°c
Max / Min Operating Pressure In The Feed Line	+0.5 to -0.6 Bar
Hydrostatic Gauge For Horizontal Tanks	Part Number: D2100
Hydrostatic Gauge For Vertical Tanks	Part Number: D2000

NEED MORE INFORMATION?